

HSF

LENGTH±TOLERANCE

P1 Male

P2 Male

Wire SPEC	LENGTH	TOLERANCE
ULxxxx 22~30AWG	1~499	±5
	500~999	±10
	1000~1500	±15
	1501~3000	±20
	3001~5000	±30
	5001~	± Lx1%

SPECIFICATIONS

Insulation Resistance:5M Ω Min
Contact Resistance:3.0 Ω Max
Withstand Voltage:DC 300V, 10S
The Cable Assembly Must 100% Test

CONNECT METHOD

P1	COLOR	P2
1	White	1
2	RED	2
3	White	3
4	GREEN	4
5	White	5
6	Orange	6
7	White	7
8	Blue	8
9	White	9
Shell	Braid	Shell

Ordering Information

C9700 - 09 02 XXXX -001

No.of Pins: 09P Shape Style: 02=Both ends Process Length of Line

⑥	GPVC-B70XG01	Plastic	PVC 45P Black/Blue/Grey	0.020	KG
⑤	GPE-W00XG01	Plastic	PE WHITE	0.008	KG
④	GPVC-B60XG01	Plastic	PVC 35P Black/Blue/Grey	0.006	KG
③		Screw	4#-4UNC	4	PCS
②	6220-09MXXXX01	D-SUB	DB9P MALE SOLDER TYPE Black/Blue	2	PCS
①	WXXXX-XXXX00001	Cable	UL2464/2919 22~30AWG*5P+AL/MYLAR+Braid PVC Jacket Black/Beige/Grey	XXX	MM
NO.	Part No.	Name	specification	Q' TY	UNIT

					工程图 ENGINEERING		绘图 DRAW	BEN	09/11/02	SCALE	Free	WCON维峰五金电子有限公司 WAFE HARDWARE ELECTRONICS CO. LTD			
					X.X	±0.30	设计 DESIGN			UNIT	mm				
					X.XX	±0.20				SIZE	A4	料号 PART NO.		C9700-0902XXXX-001	
A0	09/11/02	NEW			X.XXX	±0.10	审 核 CHECK			SHEET	1/1	品名 TITLE:		DB 9P Male TO DB9P Male	
版次 REV	日期 DATE	变 更 说 明 MODIFICATION DESCRIPTION		变更 CHANGE	核准 APPROVE	Angle DIM	± 2' TOL	核 准 APPROVE		PROJ.		客户料号Customer NO.			