

HSF

LENGTH±TOLERANCE

P1 Male

P2 Male

Wire SPEC	LENGTH	TOLERANCE
ULxxxx 22~30AWG	1~499	±5
	500~999	±10
	1000~1500	±15
	1501~3000	±20
	3001~5000	±30
	5001~	± Lx1%

SPECIFICATIONS

Insulation Resistance:10MΩ Min
Contact Resistance:2.0Ω Max
Withstand Voltage:DC 300V, 10S
The Cable Assembly Must 100% Test

CONNECT METHOD

P1	P2	COLOR	P1	P2	COLOR
1	1	ORANGE	9	9	DRAIN
2	2	YELLOW	10	10	DRAIN
3	3	BROWN	11	11	DRAIN
4	4	NC	12	12	NC
5	5	DRAIN	13	13	RED
6	6	DRAIN	14	14	BLACK
7	7	DRAIN	15	15	NC
8	8	DRAIN			

Ordering Information

C9700 - 15 02 xxxx -001

No.of Pins:
15P

Shape Style:
02=Both ends Process

Length of Line

⑥	GPVC-B70XG01	Plastic	PVC 45P Black/Blue/Grey	0.020	KG
⑤	GPE-W00XG01	Plastic	PE WHITE	0.008	KG
④	GPVC-B60XG01	Plastic	PVC 35P Black/Blue/Grey	0.006	KG
③		Screw	4#-4UNC	4	PCS
②	6210-15MXXXX01	D-SUB	HDB15P MALE SOLDER TYPE Black/Blue	2	PCS
①	WXXXX-XXXX00001	Cable	UL2464/2919 22~30AWG*5C+D+AL/MYLAR PVC Jacket Black/Beige/Grey	XXX	MM
NO.	Part No.	Name	specification	Q'TY	UNIT

					工程图 ENGINEERING	绘图 DRAW	BEN	09/11/02	SCALE	1:1	WCON 维峰五金电子有限公司 WAFE HARDWARE ELECTRONICS CO. LTD			
					X.X	±0.30			UNIT	mm				
					X.XX	±0.20			SIZE	A4	料号 PART NO.	C9700-1502XXXX-001		
					X.XXX	±0.10			SHEET	1/1	品名 TITLE:	HDB 15P Male TO HDB15P Male		
A0	09/11/02	NEW			Angle	± 2'			PROJ.		客户料号Customer NO.			
版次 REV	日期 DATE	变更说明 MODIFICATION DESCRIPTION	变更 CHANGE	核准 APPROVE	DIM	TOL	核准 APPROVE							