

HSF

LENGTH±TOLERANCE

P1 Female

P2 Female

CONNECT METHOD

P1	P2	P1	P2
1	1	14	14
2	2	15	15
3	3	16	16
4	4	17	17
5	5	18	18
6	6	19	19
7	7	20	20
8	8	21	21
9	9	22	22
10	10	23	23
11	11	24	24
12	12	25	25
13	13	SHELL	SHELL

SPECIFICATIONS

Insulation Resistance:10MΩ Min

Contact Resistance:2.0Ω Max

Withstand Voltage:DC 300V, 10S

The Cable Assembly Must 100% Test

Wire SPEC	LENGTH	TOLERANCE
ULxxxx 22~30AWG	1~499	±5
	500~999	±10
	1000~1500	±15
	1501~3000	±20
	3001~5000	±30
	5001~	± Lx1%

Ordering Information

C9700 - 25 02 xxxx -201

No.of Pins:
25P

Shape Style:
02=Both ends Process

Length of Line

⑥	GPVC-B70XG01	Plastic	PVC 45P Black/Blue/Grey	0.026	KG
⑤	GPE-W00XG01	Plastic	PE WHITE	0.008	KG
④	GPVC-B60XG01	Plastic	PVC 35P Black/Blue/Grey	0.006	KG
③		Screw	4#-4UNC	4	PCS
②	6220-25FXXXX01	D-SUB	DB25P FEMALE SOLDER TYPE Black/Blue	2	PCS
①	WXXXX-XXXX00001	Cable	UL2464/2919 22~30AWG*25C+D+AL/MYLAR PVC Jacket Black/Beige/Grey	XXX	MM
NO.	Part No.	Name	specification	Q'TY	UNIT

						工程图 ENGINEERING		绘图 DRAW	BEN	09/11/02	SCALE	1:1	WCON 维峰五金电子有限公司 WAFE HARDWARE ELECTRONICS CO. LTD		
						X.X	±0.30	设计 DESIGN			UNIT	mm			
						X.XX	±0.20	审 核 CHECK			SIZE	A4	料号 PART NO.	C9700-2502XXXX-201	
A0	09/11/02	NEW		_____	_____	X.XXX	±0.10		核 准 APPROVE			SHEET	1/1	品名 TITLE:	DB 25P Female TO DB25P Female
版次 REV	日期 DATE	变 更 说 明 MODIFICATION DESCRIPTION			变更 CHANGE	核准 APPROVE	Angle DIM	± 2' TOL	核 准 APPROVE			PROJ.		客户料号Customer NO.	